

# SFP13010PAxD – SFP Dual Fibre

## 1310nm / 10km / OC-48 Multirate

For your product safety, please read the following information carefully before any manipulation of the transceiver:



### ESD

This transceiver is specified as ESD threshold 1kV for SFI pins and 2kV for all others electrical input pins, tested per MIL-STD-883G, Method 3015.4 / JESD22-A114-A (HBM). However, normal ESD precautions are still required during the handling of this module.



### LASER SAFETY

This is a Class1 Laser Product according to IEC 60825-1:2007. This product complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated (June 24, 2007).

The optical ports of the module need to be terminated with an optical connector or with a dust plug in order to avoid contamination.

## 1. Overview

SFP13010PAxD is a high performance transceiver module for 100 Mbps to 2.67 Gbps data links over a single mode fibre pair. The maximum reach is 10km, with 6.3 dB end of life (EOL) power budget. The transmitter is a 1310nm Fabry-Pérot laser, the receiver a PIN photodiode.

This transceiver module is compliant with the Small Form-factor Pluggable (SFP) Multisource Agreement (MSA) and hot pluggable. Always contact Skylane Optics commercial agents for compatibility with different equipment platforms.

## 2. Features

- SFP Multi-Source Agreement compliant [INF-8074]
- Hot pluggable SFP footprint
- Serial ID functionality supported according to [SFF-8472]
- Class 1 laser safety standard IEC 60825 compliant
- Dual LC connector
- 1310nm FP transmitter
- PIN receiver
- 10km point-to-point transmission on single mode fibre
- SONET OC-48/SDH STM-16
- SONET OC-12/SDH STM-4
- SONET OC-3/SDH STM-1
- 1x/2x Fibre Channel
- Fast Ethernet/Gigabit Ethernet
- Operating temperature range 0°C to 70°C or -40°C to 85°C
- Low power dissipation (<1W)
- Digital diagnostics monitoring (DDM)




Figure 1. SFP Dual Fiber (non-binding illustration)

## 3. Applications

- Storage
- Datacom Ethernet
- Telecom Sonet/SDH

## 4. Optical Interface

| P/N          | Wavelength [nm] | Output Optical Power <sup>2</sup> [dBm] | Optical Receiver Sensitivity <sup>3</sup> [dBm] | Optical Receiver Overload <sup>4</sup> [dBm] | Power Budget <sup>2</sup> [dB] |
|--------------|-----------------|---|---|--|--------------------------------|
| SFP13010PAxD | 1310nm          | -11.7 to -3                             | ≤ -18   | -3   | ≥ 6.3                          |

1. Distance is estimated assuming typical optical losses after decent quality fibre deployment; Only optical budget value is guaranteed.

2. EOL, over operating temperature range

3. Measured at 2.488Gbps, PRBS 223-1, ER=9dB, BER≤10<sup>-12</sup>

4. The optical input to the receiver should not exceed this value. Transmitters must never be directly connected to receivers (optical loop back) before ensuring that proper optical attenuation is used.

## 5. Technical Parameters

### 5.1. Recommended Operating Conditions

| Parameter                  | Min  | Typ | Max  | Units | Notes          |
|----------------------------|------|-----|------|-------|----------------|
| Storage temperature        | -40  |     | 85   | °C    |                |
| Operating Case Temperature | 0    |     | 70   | °C    | SFP13010PA0D   |
|                            | -40  |     | 85   | °C    | SFP13010PA2D   |
| Relative Humidity          | 5    |     | 95   | %     | Non condensing |
| Power Supply Voltage       | 3.15 | 3.3 | 3.45 | V     |                |
| Power Supply Current       |      |     | 300  | mA    |                |

### 5.2. Transmitter Optical Specifications

| Parameter            | Min   | Typ  | Max  | Units | Notes |
|----------------------|-------|------|------|-------|-------|
| Average Output Power | -11.7 |      | -3   | dBm   | 5     |
| Centre Wavelength    | 1260  | 1310 | 1360 | nm    |       |
| Spectral Width (RMS) |       |      | 3    | nm    |       |
| Extinction Ratio     | 8.2   |      |      | dB    |       |

5. Output power coupled into a 9/125 µm multimode fiber

### 5.3. Receiver Optical Specifications

| Parameter                | Min  | Typ | Max  | Units | Notes |
|--------------------------|------|-----|------|-------|-------|
| Receiver Sensitivity     |      |     | -18  | dBm   | 6     |
| Receiver Overload        | -3   |     |      | dBm   | 6     |
| Receiver Operating Range | 1260 |     | 1600 | nm    |       |

6. Measured at 2.488Gbps, PRBS 2<sup>23</sup>-1, ER=9dB, BER≤10<sup>-12</sup>

## 6. Transceiver Electrical Pad Layout




Figure 2. Transceiver Electrical Pad Layout

7. Module Electrical Pin Definition

SFP MSA (INF-8074i)

| Pin Number | Name        | Function                      |
|------------|-------------|-------------------------------|
| 1          | VeeT        | Transmitter Ground            |
| 2          | TX Fault    | Transmitter Fault Indication  |
| 3          | TX_Disable  | Transmitter Disable           |
| 4          | MOD-DEF2    | 2-Wire Serial Interface Data  |
| 5          | MOD-DEF1    | 2-Wire Serial Interface Clock |
| 6          | MOD-DEF0    | Grounded in Module            |
| 7          | Rate Select | Not Connected                 |
| 8          | LOS         | Loss of Signal                |
| 9          | VeeR        | Receiver Ground               |
| 10         | VeeR        | Receiver Ground               |
| 11         | VeeR        | Receiver Ground               |
| 12         | RD-         | Inverted Received Data Out    |
| 13         | RD+         | Received Data Out             |
| 14         | VeeR        | Receiver Ground               |
| 15         | VccR        | Receiver Power                |
| 16         | VccT        | Transmitter Power             |
| 17         | VeeT        | Transmitter Ground            |
| 18         | TD+         | Transmit Data In              |
| 19         | TD-         | Inverted Transmit Data In     |
| 20         | VeeT        | Transmitter Ground            |

8. EEPROM

SFP MSA [INF-8072]




Figure 3. EEPROM of a an SFP

## 9. Ordering Information

| Part Number  | Description   |
|--------------|---|
| SFP13010PA0D | SFP dual fibre, Tx 1310nm (FP) , Rx (PIN), maximum distance 10km, power budget 6.3dB, OC-48 multirate, LC connector, <b>0°C to 70°C</b> , DDM   |
| SFP13010PA2D | SFP dual fibre, Tx 1310nm (FP) , Rx (PIN), maximum distance 10km, power budget 6.3dB, OC-48 multirate, LC connector, <b>-40°C to 85°C</b> , DDM |

## 10. Document Revision Information

| Revision | Description     |
|----------|-----------------|
| A        | Initial release |

Skylane Optics supplies a broad range of optical transceivers. Our engineers work closely with our customers to find the best solutions for every application. We are committed to provide high quality products and services to our customers.

For questions on this product please contact:  
[support@skylaneoptics.com](mailto:support@skylaneoptics.com)

**Beyond  
Quality**

**Reliable  
Alliance**

**Performing  
Smartly**