

# SPCxx0400H0C – SFP+ Dual Fibre CWDM

CWDM / 40km / OC-192 Multirate / CDR

For your product safety, please read the following information carefully before any manipulation of the transceiver:



**ESD**

This transceiver is specified as ESD threshold 1kV for SFI pins and 2kV for all others electrical input pins, tested per MIL-STD-883G, Method 3015.4 /JESD22-A114-A (HBM). However, normal ESD precautions are still required during the handling of this module.



**LASER SAFETY**

This is a Class1 Laser Product according to IEC 60825-1:2007. This product complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated (June 24, 2007).

The optical ports of the module need to be terminated with an optical connector or with a dust plug in order to avoid contamination.

## 1. Overview

SPCxx0400H0C is a high-performance transceiver module for OC-192 multirate data links over a single mode fibre pair. The maximum reach<sup>1</sup> is 40km, with 14dB end of life (EOL) power budget. The transmitter is a CWDM EML laser, the receiver is a PIN photodiode.

This transceiver module is compliant with the Small Form-factor Pluggable (SFP+) Multisource Agreement (MSA) and hot pluggable. Always contact Skylane Optics® commercial agents for compatibility with different equipment platforms.

## 2. Features

- Electrical interface specification as per SFF-8431
- Hot pluggable SFP+ footprint
- Management interface specification as per SFF-8431 and SFF-8472
- Class 1 laser safety standard IEC 60825 compliant
- SFP+ MSA package with duplex LC connector
- CWDM EML transmitter, 1470nm to 1610nm in 20nm step
- PIN receiver
- Built-in Tx and Rx Clock Data Recovery (CDR)
- 40km point-to-point transmission on single mode fibre
- Operating temperature range 0°C to 70°C
- Power dissipation < 1.8W
- Digital Diagnostics monitoring (DDM)




Figure 1. SFP+ Dual Fibre (non-binding illustration)

## 3. Applications

- SONET OC-192/SDH STM-64
- 10GBASE-ZR/ZW
- 10x Fiber Channel

## 4. Optical Interface

P/N	Wavelength [nm]	Optical Output Power <sup>2</sup> [dBm]	Receiver Sensitivity <sup>3</sup> [dBm]	Transmitter and Dispersion Penalty [dB]	Receiver Overload <sup>4</sup> [dBm]	Power Budget <sup>2</sup> [dB]
SPCxx0400H0C	ITU CWDM	-1 to 4	≤ -15	3	-1	≥ 14

1. Distance is estimated assuming typical optical losses after decent quality fibre deployment; Only optical budget value is guaranteed  
 2. EOL, over operating temperature range  
 3. Measured with 11.1Gbps PRBS 2<sup>31</sup>-1, BER≤10<sup>-12</sup>  
 4. The optical input to the receiver should not exceed this value. Transmitters must never be directly connected to receivers (optical loop back) before ensuring that proper optical attenuation is used

## 5. Technical Parameters

5.1. Recommended Operating Conditions					
Parameter	Min	Typ	Max	Unit	Notes
Storage temperature	-40		85	°C	
Operating Case Temperature	0		70	°C	
Relative Humidity	5		95	%	Non condensing
Power Supply Voltage	3.13	3.3	3.45	V	
Power Supply Current			455	mA	
Power Dissipation			1.5	W	

5.2. Transmitter Optical Specifications					
Parameter	Min	Typ	Max	Unit	Notes
Average Output Power	-1		4	dBm	5
Centre Wavelength Range	1464.5		1618.5	nm	
Wavelength	$\lambda_c - 6.5$	$\lambda_c$	$\lambda_c + 7.5$	nm	6
Spectral Width (-20dB)			1	nm	
Extinction Ratio	3.5			dB	
Transmitter and Dispersion Penalty (TDP)			3	dB	

5. Output power coupled into a 9/125  $\mu$ m single-mode fibre

6. ITU-T G.694.2 CWDM. For available wavelengths, see section 9

5.3. Receiver Optical Specifications					
Parameter	Min	Typ	Max	Unit	Notes
Receiver Sensitivity			-15	dBm	7
Receiver Overload	-1			dBm	7
Receiver Operating Range	1250		1620	nm	

7. Measured with 11.1Gbps PRBS 2<sup>31</sup>-1, BER $\leq$ 10<sup>-12</sup>

## 6. Transceiver Electrical Pad Layout




Figure 2. Transceiver Electrical Pad Layout

**7. Module Electrical Pin Definition**

SFP+ MSA (SFF-8431)

Pin Number	Name	Function
1	VeeT	Module Transmitter Ground
2	Tx_Fault	Module Transmitter Fault
3	Tx_Disable	Transmitter Disable
4	SDA	2-Wire Serial Interface Data
5	SCL	2-Wire Serial Interface Clock
6	Mod_ABS	Module Absent
7	RS0	Not Used
8	Rx_LOS	Receiver Loss of Signal
9	RS1	Not Used
10	VeeR	Module Receiver Ground
11	VeeR	Module Receiver Ground
12	RD-	Receiver Inverted Data Output
13	RD+	Receiver Non-Inverted Data Output
14	VeeR	Module Receiver Ground
15	VccR	Module Receiver 3.3V Supply
16	VccT	Module Transmitter 3.3V Supply
17	VeeT	Module Transmitter Ground
18	TD+	Transmitter Non-Inverted Data Input
19	TD-	Transmitter Inverted Data Input
20	VeeT	Module Transmitter Ground

**8. EEPROM**

SFP+ MSA (SFF-8472)




Figure 3. EEPROM of a SFP+

## 9. Ordering Information

Part Number	Description
SPC470400H0C	SFP+ CWDM Dual Fibre, <b>Tx 1470nm</b> (CWDM EML), Rx (PIN), maximum distance 40km, power budget 14dB, OC-192 multirate (CDR), LC connector, <b>0°C to 70°C</b> , DDM
SPC490400H0C	SFP+ CWDM Dual Fibre, <b>Tx 1490nm</b> (CWDM EML), Rx (PIN), maximum distance 40km, power budget 14dB, OC-192 multirate (CDR), LC connector, <b>0°C to 70°C</b> , DDM
SPC510400H0C	SFP+ CWDM Dual Fibre, <b>Tx 1510nm</b> (CWDM EML), Rx (PIN), maximum distance 40km, power budget 14dB, OC-192 multirate (CDR), LC connector, <b>0°C to 70°C</b> , DDM
SPC530400H0C	SFP+ CWDM Dual Fibre, <b>Tx 1530nm</b> (CWDM EML), Rx (PIN), maximum distance 40km, power budget 14dB, OC-192 multirate (CDR), LC connector, <b>0°C to 70°C</b> , DDM
SPC550400H0C	SFP+ CWDM Dual Fibre, <b>Tx 1550nm</b> (CWDM EML), Rx (PIN), maximum distance 40km, power budget 14dB, OC-192 multirate (CDR), LC connector, <b>0°C to 70°C</b> , DDM
SPC570400H0C	SFP+ CWDM Dual Fibre, <b>Tx 1570nm</b> (CWDM EML), Rx (PIN), maximum distance 40km, power budget 14dB, OC-192 multirate (CDR), LC connector, <b>0°C to 70°C</b> , DDM
SPC590400H0C	SFP+ CWDM Dual Fibre, <b>Tx 1590nm</b> (CWDM EML), Rx (PIN), maximum distance 40km, power budget 14dB, OC-192 multirate (CDR), LC connector, <b>0°C to 70°C</b> , DDM
SPC610400H0C	SFP+ CWDM Dual Fibre, <b>Tx 1610nm</b> (CWDM EML), Rx (PIN), maximum distance 40km, power budget 14dB, OC-192 multirate (CDR), LC connector, <b>0°C to 70°C</b> , DDM

## 10. Document Revision Information

Revision	Description
A	Initial release

Skylane Optics® supplies a broad range of optical transceivers. Our engineers work closely with our customers to find the best solutions for every application. We are committed to provide high quality products and services to our customers.

For questions on this product please contact:  
[support@skylaneoptics.com](mailto:support@skylaneoptics.com)

**Beyond  
Quality**

**Reliable  
Alliance**

**Performing  
Smartly**